

OCT 06 2006

## PATENT

D0932-00434  
[1-8846]

## II. Amendments to the Claims

Claims 20-43 are pending. This listing and version replaces all prior listings and versions of the claims.

1-19. (canceled)

20. (currently amended) A system for manufacturing an insulation product comprising:

a conveyor for conveying an insulation sheet containing randomly oriented fibers bonded together, said sheet having first and second major surfaces and a pair of side portions;

means for applying a layer of bicomponent fibers to at least one of said major surfaces, each of said bicomponent fibers including first component and second component portions, said applying means being coupled to a bicomponent fiber source containing said bicomponent fibers; and

a heater disposed to heat said layer and said sheet, thereby forming a nonwoven layer meltbonded to said at least one of said major surfaces.

21. (original) The system of claim 20, wherein said second component portion has a higher melting point than said first component portion, said heater heating said layer to a temperature at or above the melting temperature of said first component portion, whereby said first component portion of said bicomponent fibers is meltbonded to said randomly oriented fibers in said insulation sheet.

22. (original) The system of claim 21, wherein said sheet contains mineral fibers, polymeric fibers, rotary glass fibers, textile glass fibers, stonewool fibers, or a combination thereof.

**PATENT****D0932-00434  
[I-8846]**

23. (original) The system of claim 21, wherein said first component portion comprises a thermoplastic.
24. (original) The system of claim 21, wherein said first and second component portions are selected from the group consisting of polyethylene, polypropylene, polyester, polyethylene terephthalate, polybutylene terephthalate, polycarbonate, polyamide, polyphenylene sulfide, polyolefin, PET (polyester) PEN polyester, nylon 6,6 PCT polyester, polypropylene PBT polyester, nylon 6 co-polyamides, polylactic acid polystyrene, acetal polyurethane, and soluble copolyester HDPE, LLDPE.
25. (original) The system of claim 20, wherein said applying means includes:  
a chamber disposed above said conveying means for depositing said bicomponent fibers onto said sheet, said chamber having a side wall, a top wall, and an opening at a bottom thereof; and  
at least one blower for transmitting said bicomponent fibers to said chamber.
26. (currently amended) The system of claim 25, wherein said chamber includes at least one opening on a side thereof coupled to said blower through a hose, wherein said hose is oriented at an upward orientation toward said top wall such that the bicomponent fibers are blown into said chamber at an upward orientation toward said top wall.
27. (original) The system of claim 26, wherein said top wall includes an air filter configured to block said bicomponent fibers from escaping through said top wall.
28. (original) The system of claim 20, wherein said applying means includes a scatter coating system.
29. (currently amended) A system for applying a facing layer to an insulation product comprising:

**PATENT****D0932-00434  
[I-8846]**

a conveyor for conveying an insulation product, said insulation product comprising an insulation mat or board containing randomly oriented fibers bonded together, said product having first and second major surfaces and a pair of side portions;

means for depositing bicomponent fibers onto a first major surface of said insulation product to form a layer of bicomponent fibers thereon, each of said bicomponent fibers including first component and second component portions, said depositing means being coupled to a bicomponent fiber source containing said bicomponent fibers; and

a heater disposed to heat said deposited layer of bicomponent fibers, thereby forming a nonwoven facing layer meltbonded to said first major surface.

30. (previously presented) The system of claim 29, wherein said second component portion has a higher melting point than said first component portion, said heater heating said layer to a temperature at or above the melting temperature of said first component portion but below the melting temperature of said second component portion, whereby said first component portion of said bicomponent fibers is meltbonded to said randomly oriented fibers in said insulation product.

31. (previously presented) The system of claim 30, wherein said first component portion comprises a thermoplastic.

32. (previously presented) The system of claim 30, wherein said first and second component portions are selected from the group consisting of polyethylene, polypropylene, polyester, polyethylene terephthalate, polybutylene terephthalate, polycarbonate, polyamide, polyphenylene sulfide, polyolefin, PET (polyester) PEN polyester, nylon 6,6 PCT polyester, polypropylene PBT polyester, nylon 6 co-polyamides, polylactic acid polysterene, acetal polyurethane, and soluble copolyester HDPE, LLDPE.

**PATENT****D0932-00434  
[I-8846]**

33. (previously presented) The system of claim 29, wherein said bicomponent fibers comprise sheath-core bicomponent fibers, side-by-side bicomponent fibers, islands-in-the-sea bicomponent fibers, cospun fibers, or a combination thereof.

34. (previously presented) The system of claim 29, wherein said depositing means includes:

a chamber disposed above said conveying means for depositing said bicomponent fibers onto said insulation product, said chamber having a side wall, a top wall, and an opening at a bottom thereof; and

at least one blower for transmitting said bicomponent fibers to said chamber.

35. (previously presented) The system of claim 34, wherein said chamber includes at least one opening on a side thereof coupled to said blower through a hose, wherein said hose is oriented at an upward orientation toward said top wall.

36. (previously presented) The system of claim 35, wherein said top wall includes an air filter configured to block said bicomponent fibers from escaping through said top wall.

37. (previously presented) The system of claim 29, wherein said bicomponent fibers are deposited on said insulation product in an amount less than or equal to 2.5 grams/ft<sup>2</sup>.

38. (currently amended) A system for applying a facing layer to an insulation product comprising:

a conveyor for conveying an insulation product, said insulation product comprising an insulation mat or board containing randomly oriented fibers bonded together, said product having first and second major surfaces and a pair of side portions;

a bicomponent fiber deposition chamber disposed over said conveyor, said deposition chamber positioned to deposit bicomponent fibers onto a first major surface of said insulation

DM2\839600.1

**PATENT****D0932-00434  
[I-8846]**

product to form a layer of bicomponent fibers thereon, each of said bicomponent fibers including first component and second component portions;

a source containing of bicomponent fibers coupled to said deposition chamber; and

a heater disposed to heat said deposited layer of bicomponent fibers, thereby forming a nonwoven facing layer meltbonded to said first major surface,

wherein said second component portion has a higher melting point than said first component portion, said heater heating said layer to a temperature at or above the melting temperature of said first component portion but below the melting temperature of said second component portion, whereby said first component portion of said bicomponent fibers is meltbonded to said randomly oriented fibers in said insulation product.

39. (previously presented) The system of claim 38, wherein said first component portion comprises a thermoplastic.

40. (previously presented) The system of claim 38, wherein said first and second component portions are selected from the group consisting of polyethylene, polypropylene, polyester, polyethylene terephthalate, polybutylene terephthalate, polycarbonate, polyamide, polyphenylene sulfide, polyolefin, PET (polyester) PEN polyester, nylon 6,6 PCT polyester, polypropylene PBT polyester, nylon 6 co-polyamides, polylactic acid polystyrene, acetal polyurethane, and soluble copolyester HDPE, LLDPE.

41. (previously presented) The system of claim 38, wherein said bicomponent fibers comprise sheath-core bicomponent fibers, side-by-side bicomponent fibers, islands-in-the-sea bicomponent fibers, cospun fibers, or a combination thereof.

42. (previously presented) The system of claim 38, wherein said chamber includes at least one opening on a side thereof coupled to a blower through a hose, wherein said hose is oriented at an upward orientation toward a top wall of said chamber.

DM2\839600.1

**PATENT**

**D0932-00434  
[I-8846]**

43. (previously presented) The system of claim 38, wherein said bicomponent fibers are deposited on said insulation product in an amount less than or equal to 2.5 grams/ft<sup>2</sup>.

DM2\839600.1

7